

Turning your FLIR thermal and HD cameras to intelligent ioi devices



THE TRK-101 IS A SELF-CONTAINED SINGLE CHANNEL H.264 VIDEO ANALYTICS ENCODER.

The TRK-101 analyzes captured video signals to send alarm notifications of people, vehicles and objects that cross a perimeter line, enter a pre-defined region, are left behind or removed from a scene. Users can set customized rules and criteria to define the perimeter and what to detect.

Part of the ioi intelligent video encoder series, the TRK-101 has both analog and IP streaming video outputs (H.264, MPEG-4 SP and MJPEG) that enable hybrid connectivity to both legacy and IP-based CCTV networks. The unit can be configured through a standard web browser and set-up within five minutes.



Key Features

- Fully integrated video analysis and encoding hardware/software solution
- Automatic calibration and remote setup
- Storage on the Edge (SoE) with remote backup
- Up to five simultaneous intrusion detection rules
- Hybrid video output (analog and IP streaming)
- Site Viewer for accessing remote units over the web for live and SoE playback
- MTU setup for encrypted networks

Camera Support

- FLIR thermal cameras:
 - F-Series, FC-Series (R, S, and ID models) and TCX Series
- FLIR Quasar cameras
- Leading 3rd party cameras

Detection Types

- Intrusion:
 - PTZ target hand-off
 - Regional entrance
 - Tripwire
 - Fence trespassing
- Unattended baggage
- Object removal
- Stopped vehicle
- Loitering
- Camera tampering

Specifications

Channels	
Number of Intelligent Video Analysis Channels	1
Analog Video Output	
TV Standard	Composite 1Vp-p – NTSC or PAL
Physical Connector	1x BNC 75Ω
Digital Encoding	
IP Video Streaming	H.264, MPEG-4 SP, MJPEG
H.264 Frame Rate (PAL/NTSC)	D1 12/15 FPS
	VGA 18 FPS
	2CIF 25/30 FPS
	CIF 25/30 FPS
MPEG-4 SP Frame Rate (PAL/NTSC)	Up to 25/30 FPS for all resolutions
Bit Rate	CBR (128Kbps – 4Mbps), VBR
Storage on the Edge	3,800Mb event recording
Network	
Ethernet (IEEE 802.3/802.3u)	1 x RJ45 interface
Services and Protocols	TCP/IP, UDP/IP, HTTP, SMTP, DHCP, DNS, SNMP
Video Streaming	RTP/RTSP
Alarms/Commands	TCP/IP, HTTP
Browsers	Internet Explorer 10 and 11
Operating System	Windows 7, 8 and 8.1, 10
I/O Interface	
IN - Alarm Input	1x dry contact
OUT - Relay Output	1x relay output (rated load 0.3A@12VDC; 1A@30VDC; 0.25A@24VAC, 50/60Hz)
Power Source	
Voltage	12VDC (+/-10%), 24VAC
Power Consumption	DC: 3.6W, AC: 6W
Physical Dimensions	
Dimensions (mm)	68.5 x 36 x 118mm (W x H x D)
Dimensions (inches)	2.7 x 1.42 x 4.61" (W x H x D)
Mounting	Shelf/optional rack-mounting (single-unit or multiple-unit accessory)
Environmental Specifications	
Operating Temperature	0° to 60°C (32° to 140°F)
Operating Humidity	5% to 95% (non-condensing)
Regulatory	
Safety	UL, CE
Electromagnetic Interference	(EMC) FCC 47 CFR Part 15, Subpart B, Class A; CE Class A
Environmental	RoHS

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070

PH: +1 877.773.3547

FLIR Systems, Inc.
6769 Hollister Ave,
Goleta, CA 93117

FLIR Systems, Inc.
65 Challenger Rd
Ridgefield Pk., NJ 07660

PH: +1 201.368.9700

FLIR SYSTEMS - CANADA

250 Royal Crest Court
Markham, Ontario,
Canada L3R 3S1

PH: +1 888.425.6739

www.flir.com/security
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2017 FLIR Systems, Inc. All rights reserved. 08/06/2017