

## SX-Series LED-backlit Display 19" | 17" | 15"

### A Secure Choice for Security



Enhanced gamma correction, black-level alignment, and analogue image adjustment capabilities enable the SX-Series to display an upgraded level of surveillance images captured by conventional security cameras without any extra hassle. Crafted specifically for 24/7 security and surveillance duties, they are shielded with NeoV™ Optical Glass and metal casing, and AG Neovo's Anti-Burn-In™ technology guards them against ghosting.





### Industry-leading Reliability

The SX-Series is specially designed to transcend the challenge of enduring 24/7 operations. AG Neovo's Anti-Burn-in™ technology also prevents image ghosting while performing nonstop mission-critical operations. Its metal casing and NeoV™ Optical Glass not only protect the SX-Series from damage but also keep maintenance easy.

### Enhanced Gamma Correction

Selectable gamma curves visually optimise different kinds of images. The AG Neovo specialised image settings enhance colour, brightness, sharpness and contrast ratio, allowing the SX-Series to improve the light, shadows and colour balance of videos.



Others



AG Neovo SX-Series



### Flexible Integration

The SX-Series is equipped with DisplayPort, HDMI, DVI, VGA, Composite and S-Video for digital and analogue signal support respectively.

### Features

- Anti-Burn-in™ technology
- NeoV™ Optical Glass
- Gamma correction for image clarity even under critical sources
- Black-level alignment for presenting the delicate detail of darkness
- 3D Comb Filter/ Deinterlace/ Noise Reduction/ Freeze
- EcoSmart Sensor detects ambient lighting conditions and automatically adjusts the brightness levels
- Selectable aspect ratio and zoom function for ultimate image size
- Adjustable VGA/DVI input settings for analogue images
- Versatile inputs: DisplayPort, HDMI, DVI, VGA, Composite (BNC x2), S-Video and RS-232
- Quick signal-switching time ( $\leq 0.8$  sec.)
- Flicker-free backlight for eye comfort
- HDMI-CEC function for centralized device control
- Composite (BNC x 2) & Audio passive looping
- Available in black and white
- Front-sided IP22 rating protects screens from liquid splash and dust (19" and 17" only)
- Built-in speakers (2W x 2)
- Durable metal housing
- Rigorous screening of the components for mission-critical 24/7 applications



**SX-19E**



**SX-17E**



**SX-15E**

Specifications		SX-19E	SX-17E	SX-15E
Panel	Panel Type	LED-Backlit TFT LCD	LED-Backlit TFT LCD	LED-Backlit TFT LCD (VA Panel)
	Panel Size	19.0"	17.0"	15.0"
Panel	Max. Resolution	1280 x 1024	1280 x 1024	1024 x 768
	Pixel Pitch	0.294 mm	0.264 mm	0.297 mm
	Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
	Contrast Ratio	1000 : 1	1000 : 1	2000:1
	Viewing Angle (H/V)	170°/160°	170°/160°	176°/176°
	Display Colour	16.7 M	16.7 M	16.2 M
	Response Time	3 ms	3 ms	5 ms
	Horizontal Resolution	TV Lines	620 TVL (NTSC) 625 TVL (PAL)	620 TVL (NTSC) 625 TVL (PAL)
Frequency (H/V)	H Freq.	15 kHz - 83 kHz	15 kHz - 83 kHz	15 kHz - 83 kHz
	V Freq.	48 Hz - 85 Hz	48 Hz - 85 Hz	48 Hz - 85 Hz
Input	VGA	15-Pin D-Sub	15-Pin D-Sub	15-Pin D-Sub
	DVI	24-Pin DVI-D	24-Pin DVI-D	24-Pin DVI-D
	Composite	BNC x 2	BNC x 2	BNC x 2
	HDMI	HDMI 1.4	HDMI 1.4	HDMI 1.4
	DisplayPort	DisplayPort 1.2a	DisplayPort 1.2a	DisplayPort 1.2a
	S-Video	4-Pin mini DIN	4-Pin mini DIN	4-Pin mini DIN
USB	USB 2.0 (Service Port)	USB 2.0 (Service Port)	USB 2.0 (Service Port)	
Output	Composite	BNC x 2	BNC x 2	BNC x 2
External Control	RS-232	RS-232	RS-232	RS-232
Audio	Audio In	Stereo audio in for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1	Stereo audio in for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1	Stereo audio in for PC (3.5 mm) x 1 Stereo audio for video (RCA) x 1
	Audio Out	Stereo audio for video (RCA) x 1	Stereo audio for video (RCA) x 1	Stereo audio for video (RCA) x 1
	Speaker	2 W x 2	2 W x 2	2 W x 2
Power	Power Supply	External	External	External
	Power Requirement	DC 12 V	DC 12 V	DC 12 V
	Consumption	< 20 W (On) < 0.5W (Stand-by) < 0.5W (Off)	< 19 W (On) < 0.5W (Stand-by) < 0.5W (Off)	< 17 W (On) < 0.5W (Stand-by) < 0.5W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")	3.0 mm (0.12")	3.0 mm (0.12")
	Reflection Rate	< 1%	< 1%	< 1%
	Transmission Rate	≥97%	≥97%	≥97%
	Coating Hardness	9H	9H	9H
Plug & Play	VESA	DCC 2B, DCC/GI	DCC 2B, DCC/GI	DCC 2B, DCC/GI
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10%-90% (No condensation)	10%-90% (No condensation)	10%-90% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	5%-90% (No condensation)	5%-90% (No condensation)	5%-90% (No condensation)
Mounting	VESA FPM/PMI	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)	Yes (100 x 100 mm & 75 x 75 mm)
Ergonomics	Tilt	0°-20°	0°-20°	0°-20°
Security	Kensington Security Socket	Yes	Yes	Yes
Dimensions	Product w/o base (W x H x D)	445.4 x 420.2 x 175.0 mm (17.5" x 16.5" x 6.9")	409.4 x 398.2 x 175.0 mm (16.1" x 15.7" x 6.9")	380.0 x 359.0 x 155.0 mm (15.0" x 14.1" x 6.1")
	Packaging (W x H x D)	535.0 x 520.0 x 225.0 mm (21.1" x 20.5" x 8.9")	505.0 x 495.0 x 220.0 mm (19.9" x 19.5" x 8.7")	475.0 x 460.0 x 205.0 mm (18.7" x 18.1" x 8.1")
	Weight	Product Weight Packaged Weight	7.0 kg (15.4 lb) 8.7 kg (19.2 lb)	6.1kg (13.4 lb) 8.0 kg (17.6 lb)
Regulation Approval	Certification & Compliance	FCC, CB, CE, RoHS, WEEE, REACH, EuP/Erp	FCC, CB, CE, RoHS, WEEE, REACH, EuP/Erp	FCC, CB, CE, RoHS, WEEE, REACH, EuP/Erp
Accessories	Supplied	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Warranty Card, Quick Start Guide, Stand Base	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Warranty Card, Quick Start Guide, Stand Base	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Warranty Card, Quick Start Guide, Stand Base
Optional Accessories		Ceiling Mount: CMP-01 Wall Mounting Arm: WMA-01 Wall Mounting Kit: WMK-01, WMK-03 Desk Mounting Kit: DMC-01, DMC-02D Desk Mounting Stand: DMS-01D, DMS-01Q Height Adjustable Stand: ES-02	Ceiling Mount: CMP-01 Wall Mounting Arm: WMA-01 Wall Mounting Kit: WMK-01, WMK-03 Desk Mounting Kit: DMC-01, DMC-02D Desk Mounting Stand: DMS-01D, DMS-01Q Height Adjustable Stand: ES-02	Ceiling Mount: CMP-01 Wall Mounting Arm: WMA-01 Wall Mounting Kit: WMK-01, WMK-03 Desk Mounting Kit: DMC-01, DMC-02D Desk Mounting Stand: DMS-01D, DMS-01Q Height Adjustable Stand: ES-02

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Støvring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Poland Sales Office**

Warsaw, Poland

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[www.agneovo.com](http://www.agneovo.com)