



## SNC-311FEIF

SANTEC 3 MP mini IP dome camera  
3.6 mm fix lens, IR-LED, IP-66, PoE

### PRODUCT DESCRIPTION

#### ► Application:

The SANTEC IP mini IR dome camera is the ideal entry model into the world of SANTEC IP cameras. This camera might be small but powerful - and it is available at a moderate price. This camera is ideal for day and night applications thanks to the integrated IR LEDs. The focal length is 3.6 mm and the camera has 3 megapixel resolution, hence no detail is undetected. This camera fulfills almost all your needs thanks to features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot.

#### ► Technical specifications:

Type	IP-Mini day/night IR dome camera
Sensor type	1/3" Progressive Scan CMOS
Picture resolution (pixel)	3 MP (2048x1536)
Video codec	H.264 / MJPEG
Max. frame rate (fps)	20 at 3 MP, 25 at 2 MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Iris control	DC
Lens type	Fix lens
Focal length	3.6 mm fix lens
Sensitivity	0.01 (Color) / 0.005 (B/W) / 0 (IR)
IR cut filter	IR-Cut filter (mechanic)
Day/night mode adjustment	Auto / color / B/W
Digital noise reduction (DNR)	3DNR
Wide dynamic range (WDR)	Multi-level, digital
Privacy zones	4
Camera title	Yes

Tele Connect  
Telekommunikatie B.V.  
Franciscusweg 277, 1216 SG Hilversum  
Tel.: +31 (35) 6282245, Fax: +31 (35) 6210885  
info@teleconnect.nl, www.teleconnect.nl

### ► Technical specifications:

Management software support	Many VMS
Supported protocols	HTTP, UDP, UPNP, BONJOUR, DHCP, FTP, SMTP, RTSP
Supported software standards	ONVIF Profile S
Internal memory	No
Ethernet connector	RJ-45
Ethernet standards	10Base-T/100Base-TX
Classification	IP-66
Vandal-proof	No
Heater	No
Installation	Ceiling mount
Housing colour	White
Housing material	plastic
Integrated IR-LEDs	Yes
IR distance (m. ca.)	max. 20
Voltage	12 V DC / PoE
PoE standard	IEE 802.3af
Power consumption (watt)	4
Operating temperature (°C)	-20 to +50
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	114 x 86
Weight	400 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide

### ► Note:

SD card is not included.

### ► Recommended accessories

SANPOWER-MS01	1-Port PoE Power Supply, 15.4 watt incl. power cord
VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter